

CERTIFICATE OF COMPLIANCE

Certificate Number 20161007-AU5138
Report Reference AU5138-20090112
Issue Date 2016-OCTOBER-07

Issued to: EAGLE COMPRESSORS INC
3003 THURSTON AVE
GREENSBORO NC 27406-4516


This is to certify that AUTOMOTIVE FIRE APPARATUS EQUIPMENT
representative samples of See Addendum.

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: Standard for Automotive Fire Apparatus, NFPA 1901 (See Addendum for Edition).

Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Classification Mark should be considered as being covered by UL's Classification and Follow-Up Service.

The UL Classification Mark includes: UL in a circle: with the word "CLASSIFIED"  (as shown); a control number (may be alphanumeric) assigned by UL; a statement to indicate the extent of UL's evaluation of the product; and the product category name (product identity) as indicated in the appropriate UL Directory.

Look for the UL Classification Mark on the product.



William R. Carney, Director, North American Certification Programs

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20161007-AU5138
Report Reference AU5138-20090112
Issue Date 2016-OCTOBER-07

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Automotive fire equipment in accordance with NFPA 1901-2009

| Model No./Name | Cylinder Type | Rated Pressure (psi) | Unit Orientation | No. of Cylinders |
|--------------------------------|---------------|----------------------|------------------|------------------|
| SWX2@ / Sidewinder | SCBA | 4500 | Horizontal | 2 |
| MSSX2@ / Mobile SafeStation | SCBA | 4500 | Vertical | 2 |
| MSSX2@ / Mobile SafeStation | SCUBA | 3000 | Vertical | 2 |
| MSSX3@ / Mobile SafeStation | SCBA | 4500 | Vertical | 3 |
| MSSX3@ / Mobile SafeStation | SCUBA | 3000 | Vertical | 3 |
| CSSX2@ / Centurion SafeStation | SCBA | 4500 | Horizontal | 2 |
| CSSX2@ / Centurion SafeStation | SCUBA | 3000 | Horizontal | 1 |
| SSX3@ / SafeStation | SCBA | 4500 | Vertical | 3 |
| SSX3@ / SafeStation | SCUBA | 3000 | Vertical | 3 |
| RS@ / RaptorCFS | SCBA | 4500 | Vertical | 2 |
| RS@ / RaptorCFS | SCUBA | 3000 | Vertical | 2 |
| B3@ / BaronCFS | SCBA | 4500 | Vertical | 3 |
| B3@ / BaronCFS | SCUBA | 3000 | Vertical | 3 |

Note 1: @ - May be replaced with any alphanumeric combination per the manufacturer to specify particular accessories. Total number of characters for part number may vary.

Note 2: Models MSSX2@ and RS@ utilize the SafeStation – Two Position base unit.

Note 3: Models MSSX3@ and B3@ utilize the SafeStation – Three Position base unit.

Note 4: Model CSSX2@ utilizes the Centurion SafeStation base unit.



William R. Carney, Director, North American Certification Programs

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20161007-AU5138
Report Reference AU5138-20090112
Issue Date 2016-OCTOBER-07

Automotive fire equipment in accordance with NFPA 1901-2016

| Model No./Name | Cylinder Type | Rated Pressure (psi) | Unit Orientation | No. of Cylinders |
|--------------------------------|---------------|----------------------|------------------|------------------|
| CSSX2@ / Centurion SafeStation | SCBA | 5500 | Vertical | 2 |
| CSSX2@ / Centurion SafeStation | SCUBA | 3000 | Vertical | 1 |
| CSSX4@ / Centurion SafeStation | SCBA | 5500 | Vertical | 4 |
| CSSX4@ / Centurion SafeStation | SCUBA | 3000 | Vertical | 2 |
| SSX2@ / SafeStation | SCBA | 5500 | Vertical | 2 |
| SSX2@ / SafeStation | SCUBA | 3000 | Vertical | 1 |
| SSX2@ / SafeStation | SCBA | 5500 | Vertical | 2 |
| SSX2@ / SafeStation | SCUBA | 3000 | Vertical | 1 |
| SSX4@ / SafeStation | SCBA | 5500 | Vertical | 4 |
| SSX4@ / SafeStation | SCUBA | 3000 | Vertical | 2 |
| BH@ / BlackHawkCFS | SCBA | 5500 | Vertical | 2 |
| BH@ / BlackHawkCFS | SCUBA | 3000 | Vertical | 1 |
| RV@ / RavenCFS | SCBA | 5500 | Vertical | 4 |
| RV@ / RavenCFS | SCUBA | 3000 | Vertical | 2 |
| AQ@ / AirQuestCFS | SCBA | 5500 | Vertical | 2 or 4 |
| AQ@ / AirQuestCFS | SCUBA | 3000 | Vertical | 1 or 2 |
| HA@ / HarrierCFS | SCBA | 5500 | Vertical | 2 |
| HA@ / HarrierCFS | SCUBA | 3000 | Vertical | 1 |

Note 1: @ - May be replaced with any alphanumeric combination per the manufacturer to specify particular accessories. Total number of characters for part number may vary.

Note 2: Models CSSX2@, CSSX4@, SSX2@, SSX4@, BH@, RV@, AQ@, and HA@ utilize the Centurion SafeStation base unit.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

